## Appendix B

Metric Conversion Factors, Metric Prefixes, and Other Physical Conversion Factors

## **Metric Conversion Factors, Metric Prefixes, and Other Physical Conversion Factors**

Data presented in the *Monthly Energy Review* and in other U.S. Energy Information Administration publications are expressed predominately in units that historically have been used in the United States, such as British thermal units, barrels, cubic feet, and short tons. The metric conversion factors presented in Table B1 can be used to calculate the metric-unit equivalents of values expressed in U.S. Customary units. For example, 500 short tons are the equivalent of 453.6 metric tons (500 short tons x 0.9071847 metric tons/short ton = 453.6 metric tons).

In the metric system of weights and measures, the names of multiples and subdivisions of any unit may be derived by combining the name of the unit with prefixes, such as deka, hecto, and kilo, meaning, respectively, 10, 100, 1,000, and deci, centi, and milli, meaning, respectively, one-tenth, one-hundredth, and one-thousandth. Common metric prefixes can be found in Table B2.

The conversion factors presented in Table B3 can be used to calculate equivalents in various physical units commonly used in energy analyses. For example, 10 barrels are the equivalent of 420 U.S. gallons (10 barrels x 42 gallons/barrel = 420 gallons).

Table B1. Metric Conversion Factors

Type of Unit	U.S. Unit		Equivalent in	Metric Units
Mass	1 short ton (2,000 lb)	=	0.907 184 7	metric tons (t)
	1 long ton	=	1.016 047	metric tons (t)
	1 pound (lb)	=	0.453 592 37 <sup>a</sup>	kilograms (kg)
	1 pound uranium oxide (lb U₃Oଃ)	=	0.384 647 <sup>b</sup>	kilograms uranium (kgU)
	1 ounce, avoirdupois (avdp oz)	=	28.349 52	grams (g)
Volume	1 barrel of oil (bbl)	=	0.158 987 3	cubic meters (m³)
	1 cubic yard (yd³)	=	0.764 555	cubic meters (m³)
	1 cubic foot (ft <sup>3</sup> )	=	0.028 316 85	cubic meters (m³)
	1 U.S. gallon (gal)	=	3.785 412	liters (L)
	1 ounce, fluid (fl oz)	=	29.573 53	milliliters (mL)
	1 cubic inch (in³)	=	16.387 06	milliliters (mL)
Length	1 mile (mi)	=	1.609 344ª	kilometers (km)
	1 yard (yd)	=	0.914 4 <sup>a</sup>	meters (m)
	1 foot (ft)	=	0.304 8 <sup>a</sup>	meters (m)
	1 inch (in)	=	2.54ª	centimeters (cm)
Area	1 acre	=	0.404 69	hectares (ha)
	1 square mile (mi²)	=	2.589 988	square kilometers (km²)
	1 square yard (yd²)	=	0.836 127 4	square meters (m²)
	1 square foot (ft²)	=	0.092 903 04 <sup>a</sup>	square meters (m²)
	1 square inch (in²)	=	6.451 6 <sup>a</sup>	square centimeters (cm <sup>2</sup> )
Energy	1 British thermal unit (Btu) <sup>c</sup>	=	1,055.055 852 62ª	joules (J)
	1 calorie (cal)	=	4.186 8 <sup>a</sup>	joules (J)
	1 kilowatthour (kWh)	=	3.6ª	megajoules (MJ)
Temperature <sup>d</sup>	32 degrees Fahrenheit (°F)	=	O <sup>a</sup>	degrees Celsius (°C)
	212 degrees Fahrenheit (°F)	=	100 <sup>a</sup>	degrees Celsius (°C)

<sup>[</sup>a] Exact conversion.

Sources: • General Services Administration, Federal Standard 376B, *Preferred Metric Units for General Use by the Federal Government* (Washington, DC, January 1993), pp. 9–11, 13, and 16. • U.S. Department of Commerce, National Institute of Standards and Technology, Special Publications 330, 811, and 814. • American National Standards Institute/Institute of Electrical and Electronic Engineers, ANSI/IEEE Std268-1992, pp. 28 and 29.

<sup>[</sup>b] Calculated by the U.S. Energy Information Administration.

<sup>[</sup>c] The Btu used in this table is the International Table Btu adopted by the Fifth International Conference on Properties of Steam, London, 1956.

<sup>[</sup>d] To convert degrees Fahrenheit (°F) to degrees Celsius (°C) exactly, subtract 32, then multiply by 5/9.

Notes: • Spaces have been inserted after every third digit to the right of the decimal for ease of reading. • Most metric units belong to the International System of Units (SI), and the liter, hectare, and metric ton are accepted for use with the SI units. For more information about the SI units, see http://physics.nist/gov/cuu/Units/index.html.

Web Page: http://www.eia.gov/totalenergy/data/monthly/#appendices.

**Table B2. Metric Prefixes** 

Unit Multiple	Prefix	Symbol	Unit Subdivision	Prefix	Symbol
10 <sup>1</sup>	deka	da	10 <sup>-1</sup>	deci	d
10 <sup>2</sup>	hecto	h	10 <sup>-2</sup>	centi	С
10 <sup>3</sup>	kilo	k	10 <sup>-3</sup>	milli	m
10 <sup>6</sup>	mega	М	10 <sup>-6</sup>	micro	р
10 <sup>9</sup>	giga	G	10 <sup>-9</sup>	nano	n
10 <sup>-2</sup>	tera	Т	10 <sup>-12</sup>	pico	р
10 <sup>15</sup>	peta	Р	10 <sup>-15</sup>	femto	f
10 <sup>18</sup>	exa	E	10 <sup>-18</sup>	atto	а
	zetta	Z	10 <sup>-21</sup>	zepto	Z
10 <sup>21</sup> 10 <sup>24</sup>	yotta	Υ	10 <sup>-24</sup>	yocto	у

Web Page: http://www.eia.gov/totalenergy/data/monthly/#appendices.

Sources: U.S. Department of Commerce, National Institute of Standards and Technology, The International System of Units (SI), NIST Special Publication 330, 1991 Edition (Washington, DC, August 1991), p.10.

**Table B3. Other Physical Conversion Factors** 

Energy Source	Original Unit	Equivalent in Final Units		
Petroleum	1 barrel (bbl)	=	42ª	U.S. gallons (gal)
Coal	1 short ton 1 long ton 1 metric ton (t)	= = =	2,000° 2,240° 1,000°	pounds (lb) pounds (lb) kilograms (kg)
Wood	1 cord (cd) 1 cord (cd)	= =	1.25 <sup>b</sup> 128 <sup>a</sup>	shorts tons cubic feet (ft³)

<sup>[</sup>a] Exact conversion.

Web Page: http://www.eia.gov/totalenergy/data/monthly/#appendices.
Sources: U.S. Department of Commerce, National Institute of Standards and Technology, Specifications, Tolerances, and Other Technical Requirements for Weighing and Measuring Devices, NIST Handbook 44, 1994 Edition (Washington, DC, October 1993), pp. B-10, C-17, and C-21.

<sup>[</sup>b] Calculated by the U.S. Energy Information Administration.